BAB 1-06X 1-way tap | 6 dB | 5 … 1800 MHz | housing design 01



- ✔ Suitable for DOCSIS 3.1 and 4.0
- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ Inputs and outputs hum-suppressed
- ✔ High intermodulation suppression
- ✔ High return loss and isolation

Order information

Type	BAB 1-06X
Order no.	BAB00106X
GTIN	7611682009224
PE	1
VE	1
EU customs tariff number	85291080

Technical data

Frequency range	5 … 1800 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Surge Protection	1 kV @ 1.2/50 µs surge voltage according to IEC 61000-4-5 / 160 Vdc impulse and UM TS 41
Intermodulation ratio (EN 60728-4)	< –115 dBc @ 120 dBµV
Taps	1-fach
Tap loss	7.0 ±0.2 dB @ 10 MHz 5.9 ±0.2 dB @ 65 MHz 5.8 ±0.2 dB @ 108 MHz 5.7 ±0.2 dB @ 204 MHz 5.7 ±0.2 dB @ 258 MHz 5.7 ±0.2 dB @ 470 MHz 5.8 ±0.3 dB @ 862 MHz 6.1 ±0.3 dB @ 1218 MHz 6.2 ±0.5 dB @ 1794 MHz
Through loss	2.3 ±0.3 dB @ 10 MHz 2.3 ±0.3 dB @ 65 MHz 2.3 ±0.3 dB @ 108 MHz 2.3 ±0.3 dB @ 204 MHz 2.5 ±0.2 dB @ 258 MHz 2.6 ±0.2 dB @ 470 MHz 2.7 ±0.3 dB @ 862 MHz 2.8 ±0.3 dB @ 1218 MHz 3.5 ±0.4 dB @ 1794 MHz
Isolation	
Tap-Out	> 33 dB @ 10 … 204 MHz > 28 dB @ 204 … 862 MHz > 25 dB @ 862 … 1218 MHz > 22 dB @ 1218 … 1794 MHz
Connectors	
Connector type	F female (IEC 61169-24)
Impedance	75 Ohm
Return loss	> 20 dB @ 10 … 204 MHz > 19 dB @ 204 … 862 MHz > 17 dB @ 862 … 1218 MHz > 15 dB @ 1218 … 1794 MHz
General	
Operating temperature range	–15 °C … +60 °C
Dimensions (W × H × D) appr.	45 × 55 × 25 mm
IP code	IP67