

BAB 1-08P 1-way tap | 8 dB | 5...1218 MHz | housing design 01


- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VFKD TS 220
- ✓ Vodafone listed

Order information

Type	BAB 1-08P
Order no.	BAB00108P
GTIN	7611682005653
PE	1
VE	1
EU customs tariff number	85291080


Technical data

Frequency range	5...1218 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Intermodulation ratio (EN 60728-4)	120 dB μ V
Taps	1-fach
Tap loss	\leq 9.1 dB @ 5 ... 94 MHz \leq 8.9 dB @ 94 ... 188 MHz \leq 8.7 dB @ 188 ... 376 MHz \leq 8.7 dB @ 376 ... 752 MHz \leq 7.7 dB @ 752 ... 950 MHz \leq 7.2 dB @ 950 ... 1218 MHz
Through loss	\leq 1.4 dB @ 5 ... 94 MHz \leq 1.3 dB @ 94 ... 188 MHz \leq 1.4 dB @ 188 ... 376 MHz \leq 1.7 dB @ 376 ... 752 MHz \leq 1.9 dB @ 752 ... 950 MHz \leq 2.4 dB @ 950 ... 1218 MHz
RF connectors	
Type	F-Buchse (IEC 61169-24)
Connectors	
Connector type	F
Impedance	75 Ohm
Return loss	\geq 18 dB @ 5 ... 94 MHz \geq 16.5 dB @ 94 ... 188 MHz \geq 15 dB @ 188 ... 376 MHz \geq 13.5 dB @ 376 ... 752 MHz \geq 12 dB @ 752 ... 1218 MHz
General	
Operating temperature range	-15 °C ... +60 °C
Dimensions (W x H x D) appr.	45 x 55 x 25 mm
Weight	0.045 kg
IP code	IP67