

**BAB 4-24P 4-way tap | 24 dB | 5...1218 MHz | housing design 01**



- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VFKD TS 220
- ✓ Vodafone listed

**Order information**

Type	BAB 4-24P
Order no.	BAB00424P
GTIN	7611682005851
PE	1
VE	1
EU customs tariff number	85291080



**Technical data**

Frequency range	5...1218 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Intermodulation ratio (EN 60728-4)	120 dB $\mu$ V
Taps	4-fach
Tap loss	$\leq$ 24.5 dB @ 5 ... 94 MHz $\leq$ 24.4 dB @ 94 ... 188 MHz $\leq$ 24.3 dB @ 188 ... 376 MHz $\leq$ 24.4 dB @ 376 ... 752 MHz $\leq$ 24.5 dB @ 752 ... 950 MHz $\leq$ 24.9 dB @ 950 ... 1218 MHz
Through loss	$\leq$ 1.7 dB @ 5 ... 94 MHz $\leq$ 1.7 dB @ 94 ... 188 MHz $\leq$ 1.8 dB @ 188 ... 376 MHz $\leq$ 2.2 dB @ 376 ... 752 MHz $\leq$ 2.8 dB @ 752 ... 950 MHz $\leq$ 4.3 dB @ 950 ... 1218 MHz
<b>Connectors</b>	
Connector type	F
Impedance	75 Ohm
Return loss	$\geq$ 18 dB @ 5 ... 94 MHz $\geq$ 16.5 dB @ 94 ... 188 MHz $\geq$ 15 dB @ 188 ... 376 MHz $\geq$ 13.5 dB @ 376 ... 752 MHz $\geq$ 12 dB @ 752 ... 1218 MHz
<b>General</b>	
Operating temperature range	-15 °C ... +60 °C
Dimensions (W x H x D) appr.	70 x 55 x 25 mm
Weight	0.063 kg
IP code	IP67