

BAB 202-08 2-way tap | 8 dB | 5...1006 MHz | outdoor



- ✓ Tap method - directional coupler
- ✓ Trunk and tap DC/AC suitable with max. 65V~/10 A
- ✓ 5/8" Connectors
- ✓ Al die-cast housing with wall mounting bow
- ✓ Ingress protection code IP 55

Order information

Type	BAB 202-08
Order no.	BAB20208
GTIN	7611682258080
PE	1
VE	1
EU customs tariff number	85291080



Technical data

Frequency range	5...1006 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Isolation	≥ 25 dB
Taps	2-fach
Tap loss	8 ±1.5 dB @ 5 ... 1006 MHz
Through loss	≤ 3.5 dB @ 5 ... 40 MHz ≤ 3.8 dB @ 40 ... 470 MHz ≤ 4.2 dB @ 470 ... 862 MHz ≤ 4.3 dB @ 862 ... 1006 MHz
RF connectors	
Type	5/8"
Connectors	
Connector type	5/8"
Impedance	75 Ohm
Return loss	≥ 18 dB
General	
Operating temperature range	−15 °C ... +60 °C
Dimensions (W × H × D) appr.	140 × 120 × 80 mm
Weight	0.737 kg
IP code	IP67