

BAK 753-00 Connection cable IEC | right-angle connectors male | female | high shielded | 7.50 m



- ✓ Screening factor according to EN 60966-2-5, class A
- ✓ White, in polybag with self service card

Order information

| | |
|--------------------------|---------------|
| Type | BAK 753-00 |
| Order no. | BAK75300 |
| GTIN | 7611682017564 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85442000 |



Technical data

| | |
|---------------------------------------|---|
| Screening factor acc. to EN 60966-2-5 | Class A |
| Electrical data | |
| Frequency range | 0 ... 1006 MHz |
| Impedance | 75 Ω |
| Attenuation | 3.0 dB @ 862 MHz |
| Return loss | ≥ 16 dB @ 5 ... 862 MHz ≥ 14 dB @ 862 ... 1000 MHz |
| Screening factor | ≥ 85 dB @ 30...1000 MHz |
| Coupling resistance | < 1.6 m Ω /m @ 5 ... 30 MHz |
| Mechanical data | |
| Cable length | 7.50 m |
| Connector 1 | IEC male (right-angled) acc. EN 61169-2 |
| Connector 2 | IEC female (right-angled) acc. EN 61169-2 |
| Design | With kink protection sleeves |
| General | |
| Weight | 0.284 kg |