

BAK 999-90 Connection cable IEC | axial connectors male | female | high shielded | 10.00 m



- ✓ Screening factor according to EN 60966-2-5, class A
- ✓ White, in polybag with self service card

Order information

| | |
|--------------------------|---------------|
| Type | BAK 999-90 |
| Order no. | BAK99990 |
| GTIN | 7611682019995 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85442000 |



Technical data

| | |
|---------------------------------------|------------------------------------|
| Screening factor acc. to EN 60966-2-5 | Class A |
| Electrical data | |
| Frequency range | 0 ... 1006 MHz |
| Impedance | 75 Ω |
| Attenuation | 3.8 dB @ 862 MHz |
| Return loss | ≥ 20 dB @ 5 ... 1000 MHz |
| Screening factor | ≥ 85 dB @ 30...1000 MHz |
| Coupling resistance | < 0.9 mΩ/m @ 5 ... 30 MHz |
| Mechanical data | |
| Cable length | 10.00 m |
| Connector 1 | IEC male (axial) acc. EN 61169-2 |
| Connector 2 | IEC female (axial) acc. EN 61169-2 |
| Design | With kink protection sleeves |
| General | |
| Weight | 0.362 kg |