BSD 4-10N CATV loop-through outlet 10 dB | 5…1006 MHz



- ✔ Suitable for broadband return path
- ✔ Surface treated

Order information

Type	BSD 4-10N
Order no.	BSD00410N
GTIN	7611682007329
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Tap method	Double directional coupler
Through loss	2.5 … 4.0 dB
Trunk line	
Frequency range input	5…1006 MHz
Through loss	2,5…4,0 dB
Isolation internal	≥ 20 dB
Frequency range output	5…1006 MHz
Suitable cables (Inner conductor | outer diameter)	0.63…1.13 mm | 4.7…7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	5…1006 MHz
Tap loss	10 dB ±2 dB
Radio connector	
Connector type	IEC-female
Frequency range	5…1006 MHz
Tap loss	10 dB ±2 dB
General	
Dimensions (W × H × D) appr.	70 × 66 × 32 mm
Weight	0.091 kg

Suitable products

TZU 2-00 Cover plate | TV/R | single piece
TZU 1-00 Surface frame
TZU 2-10 Cover plate | TV/R | two-parts
TZU 1-10 Surface frame
TZU 3-00 Terminating resistor