

BSD 4-18N CATV loop-through outlet 18 dB | 5...1006 MHz



- ✓ Suitable for broadband return path
- ✓ Surface treated

Order information

Type	BSD 4-18N
Order no.	BSD00418N
GTIN	7611682007343
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Tap method	Double directional coupler
Through loss	1.5...2.5 dB
Trunk line	
Frequency range input	5...1006 MHz
Through loss	1,5...2,5 dB
Isolation internal	≥ 28 dB
Frequency range output	5...1006 MHz
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.7...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	5...1006 MHz
Tap loss	18 dB ±2 dB
Radio connector	
Connector type	IEC-female
Frequency range	5...1006 MHz
Tap loss	18 dB ±2 dB
General	
Dimensions (W × H × D) appr.	70 × 66 × 32 mm
Weight	0.091 kg

Suitable products

- [TZU 2-00 Cover plate | TV/R | single piece](#)
- [TZU 1-00 Surface frame](#)
- [TZU 2-10 Cover plate | TV/R | two-parts](#)
- [TZU 1-10 Surface frame](#)
- [TZU 3-00 Terminating resistor](#)