

BSD 21-10 Extended wideband loop-through outlet 10 dB | 5...2200 MHz | CATV



- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Suitable for broadband return path
- ✓ Easy to install
- ✓ Stripping length 8/13 mm
- ✓ Surface treated

Order information

| | |
|--------------------------|---------------|
| Type | BSD 21-10 |
| Order no. | BSD02110 |
| GTIN | 7611682002447 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85291095 |



Technical data

| | |
|--|---|
| Screening factor acc. to EN 50083-2 | Class A (+ 10 dB) |
| Tap method | Double directional coupler |
| Trunk line | |
| Frequency range input | 5...2200 MHz |
| Through loss | ≤ 3,5 dB @ 5...862 MHz ≤ 4,0 dB @ 862...2200 MHz |
| Isolation internal | ≥ 25 dB |
| Frequency range output | 5...2200 MHz |
| Suitable cables (Inner conductor outer diameter) | 0.63...1.13 mm 4.70...7.35 mm |
| TV connector | |
| Connector type | IEC-male |
| Frequency range | 5...2200 MHz |
| Tap loss | 10 dB ±1.5 dB |
| Radio connector | |
| Connector type | IEC-female |
| Frequency range | 5...2200 MHz |
| Tap loss | 10 dB ±1.5 dB |
| General | |
| Dimensions (W × H × D) appr. | 68 × 68 × 35 mm |
| Weight | 0.092 kg |

Suitable products

- [TZU 21-65 Plug-on adapter | Multimedia](#)
- [TZU 2-00 Cover plate | TV/R | single piece](#)
- [TZU 1-00 Surface frame](#)
- [TZU 2-10 Cover plate | TV/R | two-parts](#)
- [TZU 1-10 Surface frame](#)
- [TZU 3-00 Terminating resistor](#)