
BSD 21-18 Extended wideband loop-through outlet 18 dB | 5…2200 MHz | CATV



- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ Suitable for broadband return path
- ✔ Easy to install
- ✔ Stripping length 8/13 mm
- ✔ Surface treated

Order information

Type	BSD 21-18
Order no.	BSD02118
GTIN	7611682002478
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Screening factor acc. to EN 50083-2	Class A (+ 10 dB)
Tap method	Directional couple + ferrite splitter
Trunk line	
Frequency range input	5…2200 MHz
Through loss	≤ 0,9 dB @ 5…862 MHz ≤ 1,8 dB @ 862…2200 MHz
Isolation internal	≥ 15 dB
Frequency range output	5…2200 MHz
Suitable cables (Inner conductor | outer diameter)	0.63…1.13 mm | 4.70…7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	5…2200 MHz
Tap loss	18 dB ±1.5 dB
Radio connector	
Connector type	IEC-female
Frequency range	5…2200 MHz
Tap loss	18 dB ±1.5 dB
General	
Dimensions (W × H × D) appr.	68 × 68 × 35 mm
Weight	0.092 kg

Suitable products

TZU 21-65 Plug-on adapter | Multimedia
TZU 2-00 Cover plate | TV/R | single piece
TZU 1-00 Surface frame
TZU 2-10 Cover plate | TV/R | two-parts
TZU 1-10 Surface frame
TZU 3-00 Terminating resistor