BSD 963-12N Multimedia loop-through outlet 12 dB | 5…1006 MHz | CATV | DATA

- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ Suitable for broadband return path
- ✔ Easy to install
- ✔ Stripping length 8/13 mm
- ✔ Extended F socket
- ✔ Surface treaded
- ✔ Vodafone listed

Order information

Type	BSD 963-12N
Order no.	BSD96312N
GTIN	7611682001525
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Screening factor acc. to EN 50083-2	Class A (+ 10 dB)
Trunk line	
Frequency range input	5…1006 MHz
Through loss	≤ 3,5 dB
Frequency range output	5…1006 MHz
Suitable cables (Inner conductor | outer diameter)	0.63…1.13 mm | 4.70…7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	109...1006 MHz
Tap loss	12 dB ±1 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5…125 MHz
Tap loss	14 dB ±1.5 dB
DATA connector	
Connector type	F-female
Frequency range	5…1006 MHz
Tap loss	12 dB ±1 dB
General	
Dimensions (W × H × D) appr.	68 × 68 × 39 mm
Weight	0.100 kg

Suitable products

SZU 2-01 Cover plate | TV/R/DATA | single piece
TZU 1-00 Surface frame
TZU 3-01 Terminating resistor, DC-isolated