BSD 963-20N Multimedia loop-through outlet 20 dB | 5…1006 MHz | CATV | DATA



- ✔ Loop-through type with 20 dB tap loss
- ✔ Suitable for broadband return path
- ✔ Easy to install
- ✔ Stripping length 8/13 mm
- ✔ Extended F socket
- ✔ Surface treaded
- ✔ Vodafone listed

Order information

Type	BSD 963-20N
Order no.	BSD96320N
GTIN	7611682001556
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Screening factor acc. to EN 50083-2	Class A (+ 10 dB)
Trunk line	
Frequency range input	5…1006 MHz
Through loss	≤ 1,9 dB
Frequency range output	5…1006 MHz
Suitable cables (Inner conductor | outer diameter)	0.63…1.13 mm | 4.70…7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	109...1006 MHz
Tap loss	20 dB ±1 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5…125 MHz
Tap loss	21 dB ±1.5 dB
DATA connector	
Connector type	F-female
Frequency range	5…1006 MHz
Tap loss	20dB ±1 dB
General	
Dimensions (W × H × D) appr.	68 × 68 × 39 mm
Weight	0.100 kg

Suitable products

SZU 2-01 Cover plate | TV/R/DATA | single piece
TZU 1-00 Surface frame
TZU 3-01 Terminating resistor, DC-isolated