BSD 967-11X Multimedia loop-through outlet 11 dB | 5 … 1800 MHz | CATV | DATA

- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ For DOCSIS 3.1/4.0 applications
- ✔ Suitable for broadband return path
- ✔ High overvoltage protection
- ✔ High intermodulation immunity (≤ 115 dBc)
- ✔ TV port IEC male
- ✔ DATA port F female
- ✔ Vodafone listed according to VF TS 142

Order information

Type	BSD 967-11X
Order no.	BSD96711X
GTIN	7611682008326
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Screening factor acc. to EN 50083-2	Class A (+10 dB)
Trunk line	
Frequency range input	5 … 1800 MHz
Through loss	≤ 3 … 5 dB
Frequency range output	5 … 1800 MHz
Suitable cables (inner conductor | outer conductor | outer diameter)	0.4 … 1.13 mm | 3.5 … 6.0 mm | 4.70 … 7.35 mm
TV connector	
Connector type	IEC male
Frequency range	258 … 862 MHz
Tap loss	11 dB ±1 dB
DATA connector	
Connector type	F female
Frequency range	5 … 1800 MHz
Tap loss	11 dB ±1 dB
Isolation TV⊠DATA	≥ 60 dB @ 5 … 204 MHz ≥ 25 dB @ 258 … 1800 MHz
General	
Dimensions (W × H × D) appr.	68 × 68 × 39 mm
Weight	0.1 kg

Suitable products

TZU 2-01 Cover plate | TV/DATA | single piece
TZU 1-00 Surface frame
TZU 2-11 Cover plate | TV/DATA | two-parts
TZU 1-10 Surface frame