BVE 3-01P 3-way splitter | 5…1218 MHz | housing design 01



- ✔ High return loss
- ✔ For multimedia-use
- ✔ Inputs and outputs hum-suppressed
- ✔ High intermodulation suppression
- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ Return loss and isolation according to VFKD TS 220
- ✔ Vodafone listed

Order information

Type	BVE 3-01P
Order no.	BVE00301P
GTIN	7611682005608
PE	1
VE	1
EU customs tariff number	85291080

Technical data

Frequency range	5…1218 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Intermodulation ratio (EN 60728-4)	115 dBµV
Splitting	3-way
Distribution	
Distribution loss	≤ 5.2 dB @ 5 … 94 MHz ≤ 5.2 dB @ 94 … 188 MHz ≤ 5.3 dB @ 188 … 376 MHz ≤ 5.6 dB @ 376 … 752 MHz ≤ 5.7 dB @ 752 … 950 MHz ≤ 6.3 dB @ 950 … 1218 MHz
RF connectors	
Type	F-Buchse (IEC 61169-24)
Isolation	
Out-Out	≥ 22 dB @ 10 … 94 MHz ≥ 20.5 dB @ 94 … 188 MHz ≥ 19 dB @ 188 … 376 MHz ≥ 17.5 dB @ 376 … 752 MHz ≥ 17.5 dB @ 752 … 950 MHz ≥ 16 dB @ 950 … 1218 MHz
Connectors	
Connector type	F
Return loss	≥ 18 dB @ 5 … 94 MHz ≥ 16.5 dB @ 94 … 188 MHz ≥ 15 dB @ 188 … 376 MHz ≥ 13.5 dB @ 376 … 752 MHz ≥ 12 dB @ 752 … 1218 MHz
General	
Operating temperature range	–15 °C … +60 °C
Dimensions (W × H × D) appr.	72 × 50 × 26 mm
Weight	0.063 kg
IP code	IP67