

BVE 4-02P 4-way splitter | 5...1218 MHz | housing design 02



- ✓ High return loss
- ✓ For multimedia-use
- ✓ Inputs and outputs hum-suppressed
- ✓ High intermodulation suppression
- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Return loss and isolation according to VFCD TS 220
- ✓ Vodafone listed

Order information

Type	BVE 4-02P
Order no.	BVE00402P
GTIN	7611682006216
PE	1
VE	1
EU customs tariff number	85291080



Technical data

Frequency range	5...1218 MHz
Screening factor acc. to EN 50083-2	Class A + 10 dB
Intermodulation ratio (EN 60728-4)	120 dB _μ V
Splitting	4-way
Distribution	
Distribution loss	$\leq 6.9 \pm 1$ dB @ 5 ... 40 MHz $\leq 6.8 \pm 1$ dB @ 40 ... 470 MHz $\leq 7.2 \pm 1$ dB @ 470 ... 862 MHz $\leq 7.4 \pm 1$ dB @ 862 ... 1006 MHz $\leq 8 \pm 1$ dB @ 1006 ... 1300 MHz
RF connectors	
Type	F-Buchse (IEC 61169-24)
Isolation	
Out-Out	≥ 27 dB @ 5 ... 40 MHz ≥ 32 dB @ 40 ... 470 MHz ≥ 30 dB @ 470 ... 862 MHz ≥ 28 dB @ 862 ... 1006 MHz ≥ 26 dB @ 1006 ... 1300 MHz
Connectors	
Connector type	F
Return loss	≥ 20 dB @ 5 ... 40 MHz ≥ 22 dB @ 40 ... 470 MHz ≥ 20 dB @ 470 ... 862 MHz ≥ 20 dB @ 862 ... 1006 MHz ≥ 20 dB @ 1006 ... 1300 MHz
General	
Operating temperature range	-15 °C ... +60 °C
Dimensions (W × H × D) appr.	89 x 39 x 54 mm
Weight	0.165 kg
IP code	IP67