

## BVS 3-65 CATV amplifier 30 dB | 98 dB $\mu$ V



- ✓ Downstream 85...862 MHz
- ✓ Adjustable attenuator and equalizer
- ✓ Upstream 5...65 MHz, passive

### Order information

Type	BVS 3-65
Order no.	BVS00365
GTIN	7611682034035
PE	1
VE	1
EU customs tariff number	85437030



### Technical data

EMC	according to EN 50083-2, class A
<b>Downstream</b>	
Frequency range	85...862 MHz
Gain	30 dB
Max. output level CSO/CTB (CENELEC raster, 41 channels, 60 dB IMA)	98 dB $\mu$ V
Attenuation: continuously adjustable	0...20 dB
Equalization: continuously adjustable	0...18 dB
Return loss	$\geq$ 14 dB (-1.5 dB/Oktave)
Noise figure typ.	$\leq$ 7 dB
<b>Upstream</b>	
Frequency range	5...65 MHz
<b>RF connectors</b>	
Type	F-female
<b>General</b>	
Power supply	230 VAC / 50 Hz
Power indicator	LED
Power consumption	6 W
Equipotential bonding connection	4 mm <sup>2</sup>
Operating temperature range (acc. to EN 60065)	-20...+50°C
Dimensions (W x H x D) appr.	160 x 100 x 45 mm
Weight	0.478 kg
IP code	IP20

## Example of use

