

## BVS 10-02 CATV inline amplifier 10 dB



- ✓ 47...862 MHz
- ✓ In die-cast housing
- ✓ Remote feedable

### Order information


Type	BVS 10-02
Order no.	BVS01002
GTIN	7611682031041
PE	1
VE	1
EU customs tariff number	85437030



### Technical data

EMC	according to EN 50083-2, class A
Downstream	
Frequency range	47...862 MHz
Gain	10 dB
Max. output level (3rd order, EN 50083-3, 60 dB KMA)	102 dB $\mu$ V
Max. output level (2nd order, EN 50083-3, 60 dB IMA)	92 dB $\mu$ V
Return loss	$\geq$ 14 dB (-1.5 dB/Octave)
Noise figure typ.	$\leq$ 8 dB
RF connectors	
Type	F-female
Connectors	
Return loss	$\geq$ 14 (-1.5 dB/oct.)
General	
Operating temperature range (acc. to EN 60065)	-20...+50°C
Remote voltage	5/6 V=
Current consumption	$\leq$ 30 mA
Max. through-current	1000 mA
Dimensions (W x H x D) appr.	85 x 26 x 20 mm
Weight	0.066 kg

### Example of use



### Suitable products

[TZU 11-02 Power supply 6VDC/100 mA](#)

[TZU 15-04 Power inserter](#)