

BVS 14-69 CATV amplifier 40 dB | 111 dBμV CSO/CTB



- ✓ KDG 1TS140: D(4.4) full load
- ✓ Local power supply
- ✓ GaAs technology
- ✓ Downstream 85...1006 MHz
- ✓ Attenuation/equalization adjustable with PCB switches
- ✓ Interstage attenuation/equalization pluggable with jumpers
- ✓ Cable simulator BZU 80-02 pluggable
- ✓ Upstream 5...65 MHz
- ✓ Active/passive pluggable with jumpers
- ✓ Attenuation adjustable with PCB switch
- ✓ Interstage attenuation/equalization pluggable with jumpers
- ✓ Al-die-cast housing
- ✓ Test ports at in- and output

Order information


Type	BVS 14-69
Order no.	BVS01469
GTIN	7611682004014
PE	1
VE	1
EU customs tariff number	85437030



Technical data

EMC	according to EN 50083-2, class A
Classification according to 1 TS 140	D(4.4)
Downstream	
Frequency range	85...1006 MHz
Gain	40 dB
Max. output level CSO/CTB (CENELEC raster, 41 channels, 60 dB IMA)	111 dBμV
Attenuation: adjustable in 1 dB steps	0...15 dB
Equalization: adjustable in 1 dB steps	0...15 dB
Attenuation interstage: pluggable with jumpers	0 2 4 6 dB
Equalization interstage: pluggable with jumpers	0 2 4 6 dB
Return loss	≥ 18 dB (-1,5 dB/Octave)
Noise figure typ.	<7dB
Upstream	
Frequency range	5...65 MHz
Gain	30 dB
Attenuation: adjustable in 1 dB steps	0...15 dB
Equalization interstage: pluggable with jumpers	0 3 6 9 dB
Attenuation interstage: pluggable with jumpers	0 6 dB
RF connectors	
Type	F-female
Test port at in-/output	-20 ±2,5 dB/-20 ±1,0 dB
General	
Switching power supply	100...240 VAC / 50...60 Hz
Power indicator	LED
Power consumption	14 W
Equipotential bonding connection	4 mm ²
Operating temperature range (acc. to EN 60065)	-20...+50°C
Dimensions (W × H × D) appr.	182 × 146 × 71 mm
Weight	1,123 kg
Protection class	IP 54

Example of use



Suitable products

- [QEW 5-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 6-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 7-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 8-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 9-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 11-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 13-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 17-50 Earthing angle | Vodafone Kabel Deutschland approved](#)
- [QEW 25-50 Earthing angle | Vodafone Kabel Deutschland approved](#)