

BZU 40-08 Cabinet CATV max. 8 subscribers | pre-assembled



- ✓ 1 × BVS 13-69N CATV amplifier 30 dB | 100 dBμV CSO/CTB *
- ✓ 1 × BVE 8-02P 8-way splitter | 5...1218 MHz *
- ✓ 1 × QEW 9-50 Earthing angle *
- ✓ 1 × MAK 20-80 Patch cable
- ✓ 9 × MAK 30-80 Patch cable
- ✓ 1 × SZU 89-04 Double power socket
- ✓ 1 × QAS 4045 Mounting cabinet

Order information

Type	BZU 40-08
Order no.	BZU04008
GTIN	7611682004694
PE	1
VE	1
EU customs tariff number	85437030



Technical data

EMC	according to EN 50083-2, class A
Downstream	
Frequency range	85...1006 MHz
Gain	27...30 dB
Max. output level CSO/CTB (CENELEC raster, 41 channels, 60 dB IMA)	85 dBμV
Upstream	
Frequency range	5...65 MHz
Gain	25...28 dB
Connectors	
Connector type	F-female
General	
Power supply	230 VAC / 50 Hz
Power consumption	6 W
Dimensions (W × H × D) appr.	400 × 400 × 200 mm
Weight	9.300 kg