

CZU 3-00 Startup kit with accessories for CMTS 2-00



- V
- V
- 1 × BZU 65-85 Diplexer 65/85 MHz 2 × BVE 4-02P 4-way splitter | 5 ... 1218 MHz | type 02 2 × TZU 4-01 Adjustable attenuator, CATV | F-female | F-male | 0.5 ... 20 dB" 11 × MAK 20-80 Patch cable | axial F connectors male | double shielded | 0.20 m V
- V 0.20 m V
- 7 \times SAK 151-00 Quickfix cable | axial F connectors male | high shielded | 1.50 m ~
- V
- 1 × QEW 4-06 Earthing angle | single-rowed | 4-way 1 × QEW 5-50 Earthing angle | 5-way 1 × QMP 3045 perforated mounting plate | 300 × 400 mm (the components are pre-assembled and wired on it) V

Order information

Туре	CZU 3-00
Order no.	CZU00300
GTIN	7611682008760
PE	1
VE	1
Ell sustams tariff number	

EU customs tariff number

hfc

Technical data

Downstream

Frequency range	85 1006 MHz	
Attenuation	19 58 dB	
Upstream		
Frequency range	5 65 MHz	
Attenuation	17 56 dB	
General		
Dimensions (W \times H \times D) appr.	300 × 400 × 95 mm	