


EAK 51-80 Connection cable for terminal devices F | axial connectors male | Quickfix | 4-way shielded | 0.50 m



- ✓ For connecting terminal devices to multimedia wall outlets
- ✓ Screening factor according to EN 60966-2-7, class A (+ 20 dB)
- ✓ 4-fold shielded; 4G/5G protected
- ✓ DOCSIS 4.0 ready
- ✓ White, 10 pcs in polybag
- ✓ Colour-coded

Order information

Type	EAK 51-80
Order no.	EAK05180
GTIN	7611682400595
PE	1
VE	1
EU customs tariff number	



Technical data

Electrical data	
Frequency range	0 ... 1800 MHz
Impedance	75 Ω
Attenuation	< 0.14 dB @ 100 MHz < 0.38 dB @ 500 MHz < 0.54 dB @ 862 MHz < 0.60 dB @ 1000 MHz < 0.80 dB @ 1500 MHz < 0.91 dB @ 1800 MHz
Return loss	≥ 20 dB @ 5 ... 1000 MHz ≥ 18 dB @ 1000 ... 1800 MHz
Screening factor	≥ 105 dB @ 30...1000 MHz ≥ 95 dB @ 1000...1800 MHz
Coupling resistance	< 0.9 mΩ/m @ 5 ... 30 MHz
Mechanical data	
Cable length	0.50 m
Connector 1	F Quickfix male (axial) acc. IEC 61169-47
Connector 2	F Quickfix male (axial) acc. IEC 61169-47
Design	With kink protection sleeves