

## EAK 153-02 Connection cable F-IEC | 1.50 m



- ✓ Axial F male connector Quickfix | right-angled IEC male connector
- ✓ For connecting terminal devices (e. g. EoC) to the radio connector of an antenna wall socket
- ✓ Shielding factor according to EN 60966-2-5 and EN 60966-2-7, class A
- ✓ 2-way shielded
- ✓ White, in polybag

### Order information

Type	EAK 153-02
Order no.	EAK15302
GTIN	7611682401042
PE	1
VE	0
EU customs tariff number	85442000



### Technical data

Screening factor acc. to EN 60966-2-5	Class A
<b>Electrical data</b>	
Frequency range	0 ... 1006 MHz
Impedance	75 Ω
Attenuation	< 0.15 dB @ 10 MHz < 0.45 dB @ 400 MHz < 0.9 dB @ 1000 MHz
Return loss	≥ 16 dB @ 5 ... 862 MHz @ IEC ≥ 15 dB @ 862 ... 1000 MHz @ IEC ≥ 18 dB @ 5 ... 862 MHz @ F-Quick ≥ 16 dB @ 862 ... 1000 MHz @ F-Quick
Screening factor	≥ 90 dB @ 30...1000 MHz
Coupling resistance	< 1.3 mΩ/m @ 5 ... 30 MHz
<b>Mechanical data</b>	
Cable length	1.50 m
Connector 1	IEC-male (right-angled) acc. to EN 61169-2
Connector 2	F-Quickfix male (axial) acc. to IEC 61169-47
Design	With kink protection sleeves