

EAK 200-80 End device connection cable IEC | axial connectors male/female | 4-way shielded | 2,00 m



- ✓ For connecting of end devices to multimedia wall outlets
- ✓ According to VF TS 5001
- ✓ Screening factor according to EN 60966-2-7, class A (+20 dB)
- ✓ 4-fold shielded; 4G/5G protected
- ✓ DOCSIS 4.0 ready
- ✓ White, loosely packed with seal
- ✓ Colour-coded
- ✓ Vodafone listed

Order information

Type	EAK 200-80
Order no.	EAK20080
GTIN	7611682401318
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Electrical data

Frequency range	0 ... 1800 MHz
Impedance	75 Ω
Attenuation	< 0.17 dB @ 100 MHz < 0.47 dB @ 500 MHz < 0.66 dB @ 862 MHz < 0.74 dB @ 1000 MHz < 0.96 dB @ 1500 MHz < 1.09 dB @ 1800 MHz
Return loss	≥ 20 dB @ 5 ... 1000 MHz ≥ 18 dB @ 1000 ... 1800 MHz
Screening factor	≥ 105 dB @ 30...1000 MHz ≥ 95 dB @ 1000...1800 MHz
Coupling resistance	< 0.9 mΩ/m @ 5 ... 30 MHz

Mechanical data

Cable length	2.00 m
Connector 1	IEC male (axial) acc. EN 61169-2
Connector 2	IEC female (axial) acc. EN 61169-2
Design	With kink protection sleeves