


HKI 41-34 4-way HDMI-IP-Encoder



- ✓ H.264 encoding
- ✓ 4 × HDMI in 4 × SPTS
- ✓ Web-GUI
- ✓ Remote maintenance (SMARTPortal)
- ✓ 2 × power supplies (hot pluggable, redundant)

Order information

Type	HKI 41-34
Order no.	HKI04134
GTIN	7611682005868
PE	1
VE	1
EU customs tariff number	85432000



Technical data

Inputs	
Connector	4 × HDMI
Video resolution	1080p@60 Hz
IP output	
Supported protocols	UDP, HTTP, RTSP, RTMP, ONVIF
Bit rate	16 Mbit/s
Audio codecs	AAC, AAC+, AAC++, MP3
Video codecs	H.264
Interfaces	
Ethernet connectors	5 × RJ-45
Ethernet standards	IEEE 802.3, 100 Base-T @ Control IEEE 802.3, 1000 Base-T / 1 GbE @ OUT 1 ... 4
Supported configuration protocols	HTTP, AXING SMARTPortal*
General	
Operating temperature range (acc. to EN 60065)	0°C...+45°C
Operating voltage	2 × 100...240 VAC/50...60 Hz
Power consumption	25 W
Dimensions (W × H × D) appr.	482 × 267 × 47 mm
Weight	4.100 kg
Comments	* encrypted, cloud-based application for configuration, monitoring and remote maintenance

Example of use

