


## HKI 81-34 8-way HDMI-IP-Encoder



- ✓ H.264 coding
- ✓ 8 × HDMI in 8 × SPTS
- ✓ Web-based configuration, remote maintenance (SMARTPortal)
- ✓ Two redundant power supplies (hot pluggable)

### Order information

Type	HKI 81-34
Order no.	HKI08134
GTIN	7611682005882
PE	1
VE	1
EU customs tariff number	85432000



### Technical data

#### Inputs

Connector	8 × HDMI
Video resolution	1080p@60 Hz
IP output	
Supported protocols	UDP, HTTP, RTSP, RTMP, ONVIF
Bit rate	16 Mbit/s
Audio codecs	AAC, AAC+, AAC++, MP3
Video codecs	H.264
Interfaces	
Ethernet connectors	9 × RJ-45
Ethernet standards	IEEE 802.3, 100 Base-T @ Control IEEE 802.3, 1000 Base-T / 1 GbE @ OUT 1 ... 8
Supported configuration protocols	HTTP, AXING SMARTPortal*
General	
Operating temperature range (acc. to EN 60065)	0°C...+45°C
Operating voltage	2 × 100...240 VAC/50...60 Hz
Power consumption	35 W
Dimensions (W × H × D) appr.	482 × 267 × 47 mm
Weight	4.150 kg
Comments	* encrypted, cloud-based application for configuration, monitoring and remote maintenance

## Example of use

