

MIE 6-02N IP to 6 × DVB-T2 | 8Kext | 49.8 Mbps



- ✓ Modular system, includes 2 modules
- ✓ Two redundant IPTV inputs (900 Mbps) per module
- ✓ Supports SPTS and MPTS (also mixed)
- ✓ Transmodulates max. 2 × 512 input streams in 2 × 3 DVB-T2 output channels
- ✓ FFT max. 8 Kext | Bitrate max. 49.8 Mbps
- ✓ Re-Multiplexing and PID Filtering
- ✓ Program duplication
- ✓ Device redundancy configurable (software extension required)
- ✓ OTA upgrade e.g. for Set Top Boxes possible
- ✓ Interface for CASimulcrypt Server (software extension required)
- ✓ Web-based configuration, suitable for AXING SMARTPortal
- ✓ Supports SNMPv1 and SNMPv2c
- ✓ 2 × redundant power supply units (also available as 36...60 VDC version)
- ✓ 19" housing, 1RU

Order information

Type	MIE 6-02N
Order no.	MIE00602N
GTIN	7611682008715
PE	1
VE	1
EU customs tariff number	




Technical data

IPTV input	
Supported input transport streams	SPTS, MPTS (CBR/VBR)
Max. number (out of SPTS or MPTS)	2 × 512
Supported protocols	IP V4; UDP; RTP; IGMP v2, v3
Total net data rate	2 × 900 Mbps
Transportstreams	
Modifiable program information	Program name, SID remapping, PID filtering, TSID, ONID
PCR correction	automatic, adaptive, <500 ns
LCN	Yes
EPG regeneration	Yes
Encryption	DVB-CSA* DVB-CISSA* ATIS-IDSA* AES-ECB* AES-CBC*
Output	
Number of channels	2 × 3 × DVB-T2
Channels selectable	52...K69
Possible frequency shift	-4...+4 MHz (0.5 MHz steps)
Connector	2 × F-female
Test port	2 × F-female (-30 dB)
Impedance	75 Ω
Output level adjustable	85...105 dBμV
Output modulation	
Compliance	DVB-T2 (EN 302 755, mode A (single PLP)) EN 50083-9 ETSI TS 101 154 ETSI EN300 429 ETSI EN 300 744
L1 post signalling	BPSK, QPSK, 16QAM, 64QAM
Type	QPSK, QAM16, QAM64, QAM256
Supported output formats	MPEG-2/H.262, MPEG-4/H.264 and HEVC/H.265
MER	≥ 43 dB
BER	≥ 9x10 ⁻⁹
Shoulder attenuation	≥ 56 dB
C/N	≥ 45 dB
Reflection	> 14 dB
Bit rate, max	49.8 Mbps
FFT	1K, 2K, 4K, 8K, 8Kext mode

FEC type	BCH, LDPC
FEC length	16200, 64800
FEC	1/2, 3/5, 2/3, 3/4, 4/5, 5/6
Pilot pattern	PP1...PP8
Guard interval	1/4, 19/128, 1/8, 19/256, 1/16, 1/32, 1/128
Interfaces	
Ethernet connectors (LAN)	2 × 4 x RJ45
Ethernet standards	IEEE 802.3, 100 Base-T @ Control IEEE 802.3, 1000 Base-T /1 GbE @ IPTV IN1, IPTV IN2, CAS
Software control and upgrading	Via Remote Access
Supported configuration protocols	HTTP, SNMP v1, SNMP v2c, AXING SMARTPortal**
General	
Operating voltage	100...240 VAC/50...60 Hz 48 VDC
Switching power supply	2 (redundant)
Power consumption	60 W
Equipotential bonding connection	4 mm ²
Operating temperature range (acc. to EN 60065)	-10°C...+50°C
Storage temperature range (acc. to EN 60065)	-20 °C...+80 °C
Dimensions (W × H × D) appr.	480 × 43 × 275 mm
Weight	3.150 kg
Comments	* with software extension MKS 1-02 only ** switchable to DVB-T by license key *** encrypted, cloud-based application for configuration, monitoring and remote maintenance

Example of use



Suitable products

[MIS 1-11 Software extension for MIE module redundancy](#)

[MKS 1-02 Software extension for CASimulcrypt](#)