

**OVK 50-03 Pre-terminated optical cable | 50 m**



- ✓ SC/APC connector at one end
- ✓ APC ferrule at the other end
- ✓ SC connector for tool-free plugging onto ferrule included – so no field splicing
- ✓ Can be pushed, pulled or blown into ducts with an internal diameter of only 5.5 mm
- ✓ Complies with IEC 60794-1-2
- ✓ Single-Mode, ITU-T: G657A1
- ✓ Fire behaviour Dca-s3,d0,a3 acc. EN 50575:2014 + A1:2016
- ✓ Delivery on a cardboard spool

**Order information**

Type	OVK 50-03
Order no.	OVK05003
GTIN	7611682401141
PE	1
VE	1
EU customs tariff number	85447000

**Technical data**

Through loss	0.4 dB/km @ 1310 nm 0.3 dB/km @ 1550 nm
<b>Connectors</b>	
Connector type	SC/APC male to APC ferrule
<b>Mechanical data</b>	
Cable length	50 m
<b>"Mechanical Data</b>	
Bending Radius Installation   Operation	11 mm   22 mm
<b>Mechanical Data</b>	
Tensile Strength	100 N
<b>General</b>	
Operating temperature range	-30 ... 70° C
Weight	0,20 kg

## Example of use

**Montageanleitung OVK xxx-03**  
**Assembly guide OVK xxx-03**

**axing**

<p><b>1</b></p>  <p>Slide boot onto cable</p>	<p><b>2</b></p>  <p>Remove dust cap</p>
<p><b>3</b></p>  <p>Click!</p> <p>Align notches and fit black housing on the connector</p>	<p><b>4</b></p>  <p>Click!</p> <p>Align notches and fit green shell on black housing</p>
<p><b>5</b></p>  <p>Re-fit dust cap</p>	<p><b>6</b></p>  <p>Slide boot onto black housing</p>

AXING AG, Gewerbehau Moskau, CH-8262 Ramsen – info@axing.com – www.axing.com

## Suitable products

SKA 1-00 Cable dispenser