

OVK 70-03 Pre-terminated optical cable | 70 m



- ✓ SC/APC connector at one end
- ✓ APC ferrule at the other end
- ✓ SC connector for tool-free plugging onto ferrule included – so no field splicing
- ✓ Can be pushed, pulled or blown into ducts with an internal diameter of only 5.5 mm
- ✓ Complies with IEC 60794-1-2
- ✓ Single-Mode, ITU-T: G657A1
- ✓ Fire behaviour Dca-s3,d0,a3 acc. EN 50575:2014 + A1:2016
- ✓ Delivery on a cardboard spool

Order information

Type	OVK 70-03
Order no.	OVK07003
GTIN	7611682401165
PE	1
VE	1
EU customs tariff number	

Technical data





Through loss	0.4 dB/km @ 1310 nm 0.3 dB/km @ 1550 nm
Connectors	
Connector type	SC/APC male to APC ferrule
Mechanical data	
Cable length	70 m
Bending radius Installation Operation	11 mm 22 mm
Tension strength	100 N
General	
Operating temperature range	–30 ... 70° C
Weight	0,28 kg

Example of use

Montageanleitung OVK xxx-03

Assembly guide OVK xxx-03



1  Slide boot onto cable	2  Remove dust cap
3  Click! Align notches and fit black housing on the connector	4  Click! Align notches and fit green shell on black housing
5  Re-fit dust cap	6  Slide boot onto black housing

AXING AG, Gewerbehaus Moskau, CH-8262 Ramsen – info@axing.com – www.axing.com

Suitable products

SKA 1-00 Cable dispenser