

SAK 21-02 F | Quickfix | patch cable | right-angle connectors | double shielded | 0.20 m



- ✓ Screening factor according to EN 60966-2-6, class A
- ✓ White, in polybag

Order information

| | |
|--------------------------|---------------|
| Type | SAK 21-02 |
| Order no. | SAK02102 |
| GTIN | 7611682006582 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85442000 |



Technical data

| Electrical data | |
|---------------------|-----------------------------------------------------------------------------------|
| Frequency range | 0 ... 2400 MHz |
| Impedance | 75 Ω |
| Attenuation | 0.02 dB @ 50 MHz 0.08 dB @ 1000 MHz 0.12 dB @ 2050 MHz |
| Screening factor | ≥ 85 dB @ 30...1000 MHz ≥ 75 dB @ 1000...2000 MHz ≥ 65 dB @ 2000...3000 MHz |
| Coupling resistance | < 1.5 mΩ/m @ 5 ... 30 MHz |
| Mechanical data | |
| Cable length | 0.20 m |
| Connector 1 | F Quickfix male (right-angled) acc. IEC 61169-47 |
| Connector 2 | F Quickfix male (right-angled) acc. IEC 61169-47 |
| Design | With kink protection sleeves |
| General | |
| Weight | 0.024 kg |