

SAK 251-00 F | Quickfix cable | axial connectors male | high shielded | 2.50 m



Abbildung ähnlich
Similar to original product

- ✓ Screening factor according to EN 60966-2-7, class A
- ✓ White, in polybag with self service card

Order information

Type	SAK 251-00
Order no.	SAK25100
GTIN	7611682092516
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Screening factor acc. to EN 60966-2-5	Class A
Electrical data	
Frequency range	0 ... 2400 MHz
Impedance	75 Ω
Attenuation	0.01dB @ 50 MHz 0.04 dB @ 1000 MHz 0.06 dB @ 2050 MHz
Return loss	≥ 16 dB @ 5 ... 2200 MHz
Screening factor	≥ 85 dB @ 30...1000 MHz ≥ 75 dB @ 1000...2000 MHz ≥ 65 dB @ 2000...3000 MHz
Coupling resistance	< 1.5 mΩ/m @ 5 ... 30 MHz
Mechanical data	
Cable length	2.50 m
Connector 1	F Quickfix male (axial) acc. IEC 61169-47
Connector 2	F Quickfix male (axial) acc. IEC 61169-47
Design	With kink protection sleeves
General	
Weight	0.104 kg