

**SAK 501-00 F | Quickfix cable | axial connectors male | high shielded | 5.00 m**



Abbildung ähnlich  
Similar to original product

- ✓ Screening factor according to EN 60966-2-7, class A
- ✓ White, in polybag with self service card

**Order information**

Type	SAK 501-00
Order no.	SAK50100
GTIN	7611682095012
PE	1
VE	1
EU customs tariff number	85442000



**Technical data**

Screening factor acc. to EN 60966-2-5	Class A
<b>Electrical data</b>	
Frequency range	0 ... 2400 MHz
Impedance	75 Ω
Attenuation	0.5 dB @ 50 MHz 2.0 dB @ 1000 MHz 3.0 dB @ 2050 MHz
Return loss	≥ 16 dB @ 5 ... 2200 MHz
Screening factor	≥ 85 dB @ 30...1000 MHz ≥ 75 dB @ 1000...2000 MHz ≥ 65 dB @ 2000...3000 MHz
Coupling resistance	< 1.5 mΩ/m @ 5 ... 30 MHz
<b>Mechanical data</b>	
Cable length	5.00 m
Connector 1	F Quickfix male (axial) acc. IEC 61169-47
Connector 2	F Quickfix male (axial) acc. IEC 61169-47
Design	With kink protection sleeves
<b>General</b>	
Weight	0.192 kg