

SAK 751-00 F | Quickfix cable | axial connectors male | high shielded | 7.50 m



Abbildung ähnlich
Similar to original product

- ✓ Screening factor according to EN 60966-2-7, class A
- ✓ White, in polybag with self service card

Order information

Type	SAK 751-00
Order no.	SAK75100
GTIN	7611682009750
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Screening factor acc. to EN 60966-2-5	Class A
Electrical data	
Frequency range	0 ... 2400 MHz
Impedance	75 Ω
Attenuation	0.75 dB @ 50 MHz 3.00 dB @ 1000 MHz 4.50 dB @ 2050 MHz
Return loss	≥ 16 dB @ 5 ... 2200 MHz
Screening factor	≥ 85 dB @ 30...1000 MHz ≥ 75 dB @ 1000...2000 MHz ≥ 65 dB @ 2000...3000 MHz
Coupling resistance	< 1.5 mΩ/m @ 5 ... 30 MHz
Mechanical data	
Cable length	7.50 m
Connector 1	F Quickfix male (axial) acc. IEC 61169-47
Connector 2	F Quickfix male (axial) acc. IEC 61169-47
Design	With kink protection sleeves
General	
Weight	0.280 kg