

SCO 2-24 Single cable LNB | 1 x 24 user bands | 1 × legacy



- ✓ For use with single-cable SAT receivers or headends
- ✓ 2 outputs for single-cable and legacy mode
- ✓ Output frequency range 950 ... 2150 MHz
- ✓ Current consumption max. 250 mA
- ✓ For 40 mm feed mount

Order information

Type	SCO 2-24
Order no.	SCO00224
GTIN	7611682401769
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Subscriber ports

Supported standards	EN 50494, EN 50607
User bands	24
User band frequencies	975/1025/1075/1125/1175/1225/1275/1325/ 1375/1425/1475/1525/1575/1625/1675/1725/ 1775/1825/1875/1925/1975/2025/2075/2125 MHz

Connectors

Connector type	2 × F-female
----------------	--------------

Electrical data

Input frequency range	10.7 ... 11.7 GHz (low-band) 11.7 ... 12.75 GHz (high-band)
Gain	60 dB
Oscillator frequency	9.75 GHz (low-band) 10.6 GHz (high-band)
Impedance	75 Ω
Output frequency range	950 ... 2150 MHz
Noise figure	0.1 dB

Mechanical data

Diameter of feed	40 mm
------------------	-------

General

Operating temperature range	-30 ... +65 °C
Operating voltage	10.0 ... 20.0 V
Current consumption	250 mA (max.)
Weight	0.1475 kg

Example of use

