

SKB 11-13 RG11 Coaxial cable CATV | SAT | 300 m



- ✓ 3-way shielded
- ✓ Class A++ according to EN 50117-2-3
- ✓ Screening factor ≥ 105 dB @ 30...1000 MHz
- ✓ Coupling resistance ≤ 0.9 m Ω /m @ 5...30 MHz
- ✓ Inner conductor made of solid copper, diameter 1.63 mm
- ✓ Physically-foamed dielectric, diameter 7.4 mm
- ✓ Screening alum. foil, tinned copper braiding, alum. foil
- ✓ Jacket PE, black
- ✓ UV resistant
- ✓ Degressive metering
- ✓ Fire behaviour Fca acc. to EN 50575
- ✓ Suitable for underground installation in a ductwork for cables
- ✓ 300 m on wooden drum
- ✓ Compression tool and stripping tool available on request.

Order information

Type	SKB 11-13
Order no.	SKB01113
GTIN	7611682007756
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Electrical data	
Impedance	75 Ohm
Attenuation	5.4 dB / 100 m @ 200 MHz 13.5 dB / 100 m @ 1000 MHz 22.0 dB / 100 m @ 2400 MHz
Screening factor	>105 dB @ 30...1000 MHz >95 dB @ 1000...2000 MHz >85 dB @ 2000...3000 MHz
Coupling resistance	<0.9 m Ω /m @ 5...30 MHz
Mechanical data	
Inner conductor material diameter	Cu 1.63 mm
Dielectric diameter	7.3 mm
Braiding opt. coverage	144 x 0.15 mm 85%
Jacket material diameter	PE 10.3 mm
Bending radius single multiple	36 100 mm
General	
Application temperature range	-5...+50°C
Operating temperature range	-40° C ... +85° C
Fire behaviour	Fca

Suitable products

[EX 11N F-compression connector NITIN for coaxial cable with dielectric 7.2 mm](#)

[CFS 7-00 F | male crimp type](#)

[CFS 7-02 F | male screw type](#)