

SKB 75-01 Mini coaxial cable | 100 m



- ✓ For SAT or CATV indoor installation
- ✓ Fire behaviour Eca acc. to EN 50575
- ✓ Inner conductor Cu, diameter 0.65 mm
- ✓ Physically-foamed dielectric, diameter 2.7 mm
- ✓ Screening alum. foil and tinned copper braiding
- ✓ Jacket PVC, white
- ✓ Degressive metering
- ✓ 100 m on a cardboard spool

Order information

Type	SKB 75-01
Order no.	SKB07501
GTIN	7611682110753
PE	1
VE	8
EU customs tariff number	85442000



Technical data

Electrical data

Impedance	75 Ω
Attenuation	14.9 dB / 100 m @ 200 MHz 30.3 dB / 100 m @ 800 MHz 53.4 dB / 100 m @ 2400 MHz
Screening factor	>90 dB @ 30...1000 MHz >85 dB @ 1000...2000 MHz >80 dB @ 2000...3000 MHz
Coupling resistance	<20mOhm/m

Mechanical data

Inner conductor material diameter	Cu 0.65 mm
Dielectric diameter	2.7 mm
Braiding opt. coverage	80 x 0.1 mm 70%
Jacket material diameter	PVC 4.7 mm
Bending radius single multiple	14 mm 46 mm

General

Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behaviour	Eca
Weight	2.333 kg

Suitable products

[CFS 4-00 F | male screw type](#)

[CFS 20-00 F | Quickfix](#)

[SKA 1-00 Cable dispenser](#)