

SKB 88-01 Coaxial cable | 2-way shielded | 100 m



- ✓ For SAT or CATV indoor installation
- ✓ Fire behaviour Eca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.7 mm
- ✓ Screening aluminium foil/aluminium braiding
- ✓ Jacket PVC, white
- ✓ Degressive metering
- ✓ 100 m on a cardboard spool

Order information

Type	SKB 88-01
Order no.	SKB08801
GTIN	7611682000054
PE	1
VE	4
EU customs tariff number	85442000



Technical data

Electrical data	
Impedance	75 Ω
Attenuation	8.4 dB / 100 m @ 200 MHz 17.8 dB / 100 m @ 800 MHz 32.1 dB / 100 m @ 2400 MHz
Screening factor	> 85 dB @ 30...1000 MHz > 80 dB @ 1000...2000 MHz > 80 dB @ 2000...3000 MHz
Coupling resistance	<16m0hm/m
Mechanical data	
Inner conductor material diameter	StCu 1.02 mm
Dielectric diameter	4.7 mm
Braiding opt. coverage	64 x 0.12 mm 45%
Jacket material diameter	PVC 6.8 mm
Bending radius single multiple	24 mm 68 mm
General	
Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behaviour	Eca
Weight	3.685 kg

Suitable products

- [SKA 1-00 Cable dispenser](#)
- [CKS 7-48 IEC | male | compression](#)
- [CKK 7-48 IEC | female | compression](#)
- [CFS 97-48 F | male | compression](#)
- [CFS 99-48 F | male | compression | Quickfix](#)
- [CFS 100-48 F | male | compression | Quickfix](#)
- [CFS 93-48 F | Opti-fix | male | self compression](#)
- [SZU 11-01 Water protection sleeve](#)