

SKB 395-04 Coaxial cable | 3-way shielded | 250 m



- ✓ For SAT or CATV indoor installation
- ✓ Class A+ according to EN 50117-2-4
- ✓ Fire behaviour Eca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.6 mm
- ✓ Screening aluminium foil, bonded/aluminium braiding/aluminium foil
- ✓ Jacket PVC, white
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 250 m in a opti-box

Order information

| | |
|--------------------------|---------------|
| Type | SKB 395-04 |
| Order no. | SKB39504 |
| GTIN | 7611682113976 |
| PE | 1 |
| VE | 2 |
| EU customs tariff number | 85442000 |



Technical data

Electrical data

| | |
|---------------------|---|
| Impedance | 75 Ω |
| Attenuation | 8.7 dB / 100 m @ 200 MHz 18.0 dB / 100 m @ 800 MHz 32.9 dB / 100 m @ 2400 MHz |
| Screening factor | >100 dB @ 30...1000 MHz >100 dB @ 1000...2000 MHz >100 dB @ 2000...3000 MHz |
| Coupling resistance | <2.5mOhm/m |

Mechanical data

| | |
|-------------------------------------|--------------------|
| Inner conductor material diameter | StCu 1.02 mm |
| Dielectric diameter | 4.6 m |
| Braiding opt. coverage | 80 x 0.12 mm 55% |
| Jacket material diameter | PVC 6.8 mm |
| Bending radius single multiple | 24 mm 68 mm |

General

| | |
|-------------------------------|-------------|
| Application temperature range | -5...+50°C |
| Operating temperature range | -20...+75°C |
| Fire behaviour | Eca |
| Weight | 10.660 kg |

Suitable products

- [TZU 20-01 Carrying strap](#)
- [CKS 7-48 IEC | male | compression](#)
- [CKK 7-48 IEC | female | compression](#)
- [CFS 97-48 F | male | compression](#)
- [CFS 99-48 F | male | compression | Quickfix](#)
- [CFS 100-48 F | male | compression | Quickfix](#)
- [CFS 93-48 F | Opti-fix | male | self compression](#)
- [SZU 11-01 Water protection sleeve](#)