SKB 395-04 Coaxial cable | 3-way shielded | 250 m



- ✔ For SAT or CATV indoor installation
- ✔ Class A+ according to EN 50117-2-4
- ✔ Fire behaviour Eca acc. to EN 50575
- ✔ Inner conductor StCu, diameter 1.02 mm
- ✔ Physically-foamed dielectric, diameter 4.6 mm
- ✔ Screening aluminium foil, bonded/aluminium braiding/aluminium foil
- ✔ Jacket PVC, white
- ✔ UV resistent
- ✔ Degressive metering
- ✔ 250 m in a opti-box

Order information

Type	SKB 395-04
Order no.	SKB39504
GTIN	7611682113976
PE	1
VE	2
EU customs tariff number	85442000

Technical data

Electrical data	
Impedance	75 Ω
Attenuation	5.9 dB / 100 m @ 87 MHz 20.4 dB / 100 m @ 862 MHz 21.8 dB / 100 m @ 950 MHz 33.3 dB / 100 m @ 2200 MHz
Screening factor	>100 dB @ 30…1000 MHz >100 dB @ 1000…2000 MHz >100 dB @ 2000…3000 MHz
Coupling resistance	<2.5mOhm/m
Mechanical data	
Inner conductor material | diameter	StCu | 1.02 mm
Dielectric diameter	4.6 m
Braiding | opt. coverage	80 x 0.12 mm | 55%
Jacket material | diameter	PVC | 6.8 mm
Bending radius single | multiple	24 mm | 68 mm
General	
Application temperature range	–5…+50°C
Operating temperature range	–20…+75°C
Fire behaviour	Eca
Weight	10.660 kg

Suitable products

TZU 20-01 Carrying strap
CKS 7-48 IEC | male | compression
CKK 7-48 IEC | female | compression
CFS 97-48 F | male | compression
CFS 99-48 F | male | compression | Quickfix
CFS 100-48 F | male | compression | Quickfix
CFS 93-48 F | Opti-fix | male | self compression
SZU 11-01 Water protection sleeve