

SKB 395-10 10 m Anschluss-Kit | 3-fach geschirmt



- ✓ For indoor installation
- ✓ Inner conductor StCu, diameter 1,02 mm
- ✓ Physically-foamed dielectric, diameter 4,6 mm
- ✓ Screening aluminium foil/aluminium braiding
- ✓ Jacket PVC, white
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 2 × waterproof F plug (1 × preassembled)
- ✓ 1 × protective rubber sleeve (1 × preassembled)

Order information

Type	SKB 395-10
Order no.	SKB39510
GTIN	7611682001471
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Electrical data

Impedance	75 Ω
Attenuation	8,8 dB / 100 m @ 200 MHz 18,3 dB / 100 m @ 800 MHz 33,8 dB / 100 m @ 2400 MHz
Screening factor	>100 dB @ 30...1000 MHz >100 dB @ 1000...2000 MHz >100 dB @ 2000...3000 MHz
Coupling resistance	<2,5mOhm/m

Mechanical data

Dielectric diameter	4,8 mm
Braiding opt. coverage	80 x 0,12 mm 55%
Bending radius single multiple	24 mm 68 mm

General

Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behavior	FCA
Weight	0,457 kg