

SKB 395-13 Coaxial cable | 3-way shielded | 500 m



- ✓ For SAT or CATV indoor installation
- ✓ Class A+ according to EN 50117-2-4
- ✓ Fire behaviour Eca acc. to EN 50575
- ✓ Inner conductor StCu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.6 mm
- ✓ Screening aluminium foil, bonded/aluminium braiding/aluminium foil
- ✓ Jacket PE, black
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 500 m on wooden drum

Order information

Type	SKB 395-13
Order no.	SKB39513
GTIN	7611682002522
PE	1
VE	1
EU customs tariff number	85442000



Technical data

Electrical data

Impedance	75 Ω
Attenuation	8.7 dB / 100 m @ 200 MHz 18.0 dB / 100 m @ 800 MHz 32.9 dB / 100 m @ 2400 MHz
Screening factor	>100 dB @ 30...1000 MHz >100 dB @ 1000...2000 MHz >100 dB @ 2000...3000 MHz
Coupling resistance	<2.5mOhm/m

Mechanical data

Inner conductor material diameter	StCu 1.02 mm
Dielectric diameter	4.6 mm
Braiding opt. coverage	80 x 0.12 mm 55%
Jacket material diameter	PE 6.8 mm
Bending radius single multiple	24 mm 68 mm

General

Application temperature range	-5...+50°C
Operating temperature range	-20...+75°C
Fire behaviour	Eca
Weight	15.860 kg

Suitable products

[CKS 7-48 IEC | male | compression](#)
[CKK 7-48 IEC | female | compression](#)
[CFS 97-48 F | male | compression](#)
[CFS 99-48 F | male | compression | Quickfix](#)
[CFS 100-48 F | male | compression | Quickfix](#)
[CFS 93-48 F | Opti-fix | male | self compression](#)
[SZU 11-01 Water protection sleeve](#)