

SKM 2-03 Audio/Video-Modulatorkassette | Twin | AV - DVB-T



- ✓ Audio/video inputs for CCD cameras, video cameras, DVD player etc.
- ✓ Adjacent channel compatible
- ✓ Programming with the remote control unit SKZ 10-00

Order information

Type	SKM 2-03
Order no.	SKM00203
GTIN	7611682002836
PE	1
VE	1
EU customs tariff number	85255000



Technical data

Inputs	
Connector	Cinch, Mini-DIN-S-Video
Video level	1 Vss
Video impedance	75 Ohm
Audio level typ.	500 mV eff.
Audio impedance typ.	4,7 kOhm

Processable signals 2 × FBAS/S-Video/RGB/YPbPr

Output

Number of channels	2 × DVB-T
Frequency range	111...862 MHz
Channels selectable	S2...K69
Connector	1 × F-male, quickfix
Impedance	75 Ω
Output level adjustable	85...105 dBμV

Output modulation

Type	IFFT 2k mode, QPSK, QAM16, QAM64
FEC	1/2, 2/3, 3/4, 5/6, 7/8 @ DVB-T
Guard interval	1/32

General

Operating voltage	16 VDC
Current consumption	1A
Operating temperature range (acc. to EN 60065)	-10°C...+50°C
Dimensions (W × H × D) appr.	72 × 218 × 129 mm
Weight	1,170 kg

Suitable products

[SKZ 10-00 Remote control](#)

[SKZ 5-01 Switching power supply for headend modules | 10 A](#)

[CFA 7-01 Earth connection block single F | F | wall mounting](#)