

SPU 21-01 DiSEqC switch | indoor



- ✓ 2 in 1
- ✓ Cascadable
- ✓ With sliding switch to determine between "Option", Tone Burst / "Position" and 22 kHz / "Band"

Order information

| | |
|--------------------------|---------------|
| Type | SPU 21-01 |
| Order no. | SPU02101 |
| GTIN | 7611682130218 |
| PE | 1 |
| VE | 1 |
| EU customs tariff number | 85291095 |



Technical data

Inputs

| | |
|-----------------------------------|----------------------------------|
| Number | 2 |
| Frequency range | 5 ... 862 MHz 950 ... 2200 MHz |
| Isolation SAT inputs SAT inputs | ≥ 25 dB |

Subscriber ports

| | |
|------------------------|---|
| Number | 1 |
| Switch commands | Band (22kHz) Position (Tone Burst) Option |
| Supported DiSEqC level | 1.0 2.0 |
| Tap loss SAT | ≤ 2 dB |

Connectors

| | |
|----------------|---|
| Connector type | F |
|----------------|---|

General

| | |
|--|------------------|
| Operating temperature range (acc. to EN 60065) | -20...+50°C |
| Dimensions (W × H × D) appr. | 110 × 80 × 35 mm |
| Weight | 0.142 kg |

Example of use

