

SPU 58-05 Multiswitch | 5 in 8 | basic-line



- ✓ For up to 8 subscribers
- ✓ Active satellite path, passive terrestrial path
- ✓ Suitable for broadband return path (EoC suitable up to 204 MHz)
- ✓ Suitable for Quad LNB
- ✓ Switching power supply

Order information

Type	SPU 58-05
Order no.	SPU05805
GTIN	7611682130591
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Inputs	
Number	5
Frequency range	5 ... 862 MHz 950 ... 2200 MHz
Isolation V H	25 dB
Isolation SAT inputs SAT inputs	30 dB
Isolation TERR SAT	50 dB
Subscriber ports	
Number	8
Tap loss TERR	20 dB
Isolation	35 dB
Max. output level SAT (3rd order SAT EN 500833 35dB KMA, 2 sender test method)	90 dB μ V
Connectors	
Connector type	F
General	
Operating temperature range (acc. to EN 60065)	-20...+50°C
Switching power supply	90...250 V~ 47-63 Hz 18 V=0.5 A
Power consumption	4.7 W
Equipotential bonding connection	4 mm ²
Dimensions (W x H x D) appr.	275 x 125 x 50 mm
Weight	0.640 kg
IP code	IP20

