

SPU 924-09S Multiswitch stand-alone/cascade unit | 9 in 24 | premium-line



- ✓ For up to 24 subscribers
- ✓ SAT active, CATV path active switchable and adjustable
- ✓ Suitable for broadband return channel with passive CATV path (suitable for EoC up to 204 MHz)
- ✓ With passive CATV path and Quattro LNB receiver-powered - no power supply unit required
- ✓ With active CATV path or Quad LNB, power supply via external power supply unit SZU 99-09S (not included) or via the SAT IF trunk lines
- ✓ Advanced standby and energy saving functionalities (e.g. only the required LNB is powered)
- ✓ USB-C port for external power supply unit
- ✓ Cascadable (unused cascade outputs must be terminated with DC-decoupled 75 Ohm terminating resistors (e.g. CFA 11-00, not included in the scope of delivery))

Order information

Type	SPU 924-09S
Order no.	SPU92409S
GTIN	7611682400731
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Inputs	
Number	9
Frequency range	5 ... 862 MHz 950 ... 2200 MHz
Max. LNB current	2000 mA
Attenuator CATV adjustment range, switchable to passive	0 ... 20 dB
Isolation V H	30 dB
Isolation CATV SAT	30 dB
Subscriber ports	
Number	24
Switch commands	13V,18V,13V/22kHz,18V/22kHz, DiSEqC 2.0
Tap loss CATV active	0 dB
Tap loss CATV passive	34 dB
Max. output level SAT (3rd order SAT EN 50083-3 35dB KMA, 2 sender test method)	100 dB μ V
Max. output level CATV (3rd order, EN 50083-3, 60 dB KMA)	90 dB μ V
Current consumption per port (without LNB supply)	50 mA
Trunk outputs	
Number	9
Max. output level CATV (3rd order EN 50083-3, 60 dB KMA)	103 dB μ V
Through loss CATV active	-23 dB
Through loss CATV passive	8 dB
Through loss SAT	3 dB
Connectors	
Connector type	F-female
General	
Operating temperature range (acc. to EN 60065)	-20 ... +55° C
Operating voltage	15 ... 20 VDC*
Equipotential bonding connection	4 mm ²
Dimensions (W x H x D) appr.	178 x 350 x 65 mm
Weight	1.080 kg
IP code	IP20
Comments	*USB-C power supply units must fulfil the Power Delivery (PD) standard and have an output voltage of 20 VDC

Suitable products

[QFW 9-10S Earthing angle | surge protection | 9-way](#)

[QFW 12-09S Earthing angle | 12-way](#)

[QFW 13-09S Earthing angle | 13-way](#)

[CFA 11-00 Terminating resistor | 75 Ohm | DC isolated](#)

[CFA 4-01N Adapter F | F | Quickfix | 36 mm](#)

[SZU 99-09S Switching mode power supply 18 V=2 A](#)