

SSD 2-10 SAT loop-through outlet 10 dB | 5...2200 MHz | CATV | SAT



- ✓ Suitable for return path 5...65 MHz
- ✓ F connector gold-plated
- ✓ With cover plate and frame

Order information

Type	SSD 2-10
Order no.	SSD00210
GTIN	7611682180206
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input	5...2200 MHz
Through loss	2...5 dB
Isolation internal	20...40 dB
Frequency range output	5...2200 MHz
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.70...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	174...862 MHz 5...65MHz
Tap loss	≤ 10 dB ≤ 11 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5...125 MHz
Tap loss	≤ 10 dB
SAT connector	
Connector type	F female
Frequency range	950...2200 MHz
DC power pass to trunk	yes
General	
Dimensions (W × H × D) appr.	78 × 78 × 44 mm
Weight	0.149 kg

Suitable products

[TZU 3-01 Terminating resistor, DC-isolated](#)