

SSD 4-00 SAT twin end outlet 5...2200 MHz | CATV | SAT | SAT



- ✓ Suitable for return path 5...65 MHz
- ✓ With cover plate and frame

Order information

Type	SSD 4-00
Order no.	SSD00400
GTIN	7611682180046
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input right	5...2200 MHz
Frequency range input left	5...2200 MHz
Isolation internal	≥ 20 dB
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.70...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	125...862 MHz 5...65MHz
Tap loss	≤ 2 dB ≤ 2 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5...125 MHz
Tap loss	≤ 2 dB
SAT connector left	
Connector type	F-female
Frequency range	950...2200 MHz
Tap loss	≤ 2 dB
DC power pass to trunk	yes
SAT connector right	
Connector type	F-female
Frequency range	5...2200 MHz
Tap loss	≤ 2 dB
DC power pass to trunk	yes
General	
Dimensions (W × H × D) appr.	78 × 78 × 46 mm
Weight	0.149 kg