
SSD 6-18 Programmable single cable loop-through outlet 14 dB | 5 … 2200 MHz | CATV | SAT



- ✔ Class A (+10 dB) according to EN 50083-2
- ✔ Suitable for return path 5 … 65 MHz
- ✔ Suitable for Unicable I (EN50494) and Unicable II (EN50607)
- ✔ Each socket can be allocated to one ore more user-bands (programming with the SZU 60-00 programmer and the free-of charge software AnDoKon (www.axing.com | download))
- ✔ Easy to install
- ✔ Stripping length 8/13 mm
- ✔ Extended F socket
- ✔ Surface treated

Order information

Type	SSD 6-18
Order no.	SSD00618
GTIN	7611682002324
PE	1
VE	1
EU customs tariff number	85291095

Technical data

Screening factor acc. to EN 50083-2	Class A (+ 10 dB)
Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input	5 … 2200 MHz
Through loss	≤ 1,3 dB @ 5…862 MHz ≤ 2,5 dB @ 862…2200 MHz
Frequency range output	5 … 2200 MHz
DC power pass	yes
Suitable cables (Inner conductor | outer diameter)	0.63 … 1.13 mm | 4.70 … 7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	109 … 862 MHz | 5 … 65MHz
Tap loss	18 dB ±1.5 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5 … 108 MHz
Tap loss	20 dB ±2.0 dB
SAT connector	
Connector type	F female
Frequency range	950 … 2200 MHz
DC power pass to trunk	yes
General	
Dimensions (W × H × D) appr.	68 × 68 × 39 mm
Weight	0.102 kg

Suitable products

SZU 60-00 Antenna wall outlet programmer for SSD 6-xx
SZU 2-00 Cover plate | TV/R/SAT | single piece
TZU 1-00 Surface frame
SZU 2-10 Cover plate | TV/R/SAT | two-parts
TZU 1-10 Surface frame
TZU 3-01 Terminating resistor, DC-isolated