


SSD 7-00 SAT twin end outlet 5...2200 MHz | CATV | SAT | SAT



- ✓ Class A (+10 dB) according to EN 50083-2
- ✓ Suitable for return path 5...65 MHz
- ✓ Suitable for Unicable I (EN50494) and Unicable II (EN50607)
- ✓ Easy to install
- ✓ Stripping length 8/13 mm
- ✓ Extended F sockets
- ✓ Surface treading
- ✓ Vodafone listed

Order information

Type	SSD 7-00
Order no.	SSD00700
GTIN	7611682002751
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Screening factor acc. to EN 50083-2	Class A (+10 dB)
Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input right	950...2200 MHz
Frequency range input left	5...2200 MHz
Isolation internal	≥ 30 dB
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.70...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	109...862 MHz 5...65MHz
Tap loss	2 dB ±1.0 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5...125 MHz
Tap loss	2 dB ±1.0 dB
SAT connector left	
Connector type	F-female
Frequency range	950...2200 MHz
Tap loss	2 dB ±1.0 dB
DC power pass to trunk	yes
SAT connector right	
Connector type	F-female
Frequency range	950...2200 MHz
Tap loss	2 dB ±1.0 dB
DC power pass to trunk	yes
General	
Dimensions (W × H × D) appr.	68 × 68 × 39 mm
Weight	0.107 kg

Suitable products

SZU 2-04 Cover plate | TV/R/SAT/SAT | single piece

TZU 1-00 Surface frame

SZU 2-14 Cover plate | TV/R/SAT/SAT | two-parts

TZU 1-10 Surface frame