

SVS 4-01 SAT inline amplifier | 47...862 MHz | 950...2400 MHz | 12...14 dB | 14...17 dB



- ✓ Wideband-compatible
- ✓ Broadband type
- ✓ DC bypass
- ✓ 22 kHz-compatible
- ✓ DiSEqC-compatible
- ✓ Singlecable-compatible
- ✓ Power supply via the coaxial cable

Order information

Type	SVS 4-01
Order no.	SVS00401
GTIN	7611682401547
PE	1
VE	1
EU customs tariff number	85437030



Technical data

EMC	according to EN 50083-2, class A
Frequency range	47 ... 862 MHz 950 ... 2400 MHz
Gain	12 dB 13 ... 17 dB
Equalization	0 dB 4 dB
Output	
Max. output level TERR (3rd order, EN 50083-3, 60 dB KMA)	102 dB μ V
Max. output level SAT (3rd order SAT, EN 50083-3, 35 dB KMA)	113 dB μ V
Noise figure	6 dB
RF connectors	
Type	F-female
General	
DC power pass	yes
Remote voltage	14 ... 18 VDC
Current consumption	45 mA \pm 5 mA
Max. through-current	500 mA
Dimensions (W x H x D) appr.	85 x 26 x 20 mm
Weight	0.050 kg

Example of use

