

SKQ 2-06 COFDM/QAM | QAM stereo twin module



- ✓ Two independent tuner inputs
- ✓ Transmodulates two COFDM/QAM signals into QAM output signals (remux)
- ✓ Decoding of encoded programs possible by using a CA module
- ✓ Adjacent channel compatible
- ✓ Programmable with remote control unit SKZ 10-00

Order information

|                          |               |
|--------------------------|---------------|
| Type                     | SKQ 2-06      |
| Order no.                | SKQ00206      |
| GTIN                     | 7611682003031 |
| PE                       | 1             |
| VE                       | 1             |
| EU customs tariff number | 85256000      |



Technical data

|                 |                 |
|-----------------|-----------------|
| Inputs          |                 |
| Number of tuner | 2 × DVB-T/DVB-C |
| Connector       | 2 × F female    |
| Frequency range | 48...862 MHz    |
| Input level     | 45...85 dBµV    |
| CI slots        | 2               |

|                                                |                               |
|------------------------------------------------|-------------------------------|
| Input modulation                               |                               |
| Error correction                               | auto                          |
| Symbol rate                                    | 1...8 MS/s                    |
| Output                                         |                               |
| Number of channels                             | 2 × DVB-C                     |
| Frequency range                                | 111...862 MHz                 |
| Channels selectable                            | 52...K69                      |
| Connector                                      | 2 × F-male, quickfix          |
| Impedance                                      | 75 Ω                          |
| Output level adjustable                        | 85...105 dBμV                 |
| Output modulation                              |                               |
| Type                                           | 32QAM, 64QAM, 128QAM, 256-QAM |
| MER                                            | ≤ 40 dB                       |
| Symbol rate                                    | 1-8 M'Symbol/sec              |
| Interfaces                                     |                               |
| Configuration interface                        | 2 × USB 1                     |
| General                                        |                               |
| Current consumption                            | 16V=1,2 A                     |
| Operating temperature range (acc. to EN 60065) | -10°C...+50°C                 |
| Dimensions (W × H × D) appr.                   | 72 × 218 × 129 mm             |
| Weight                                         | 1,520 kg                      |

## Suitable products

[SKZ 10-00 Remote control](#)

[SKZ 5-01 Switching power supply for headend modules | 10 A](#)

[CFA 7-01 Earth connection block single F | F | wall mounting](#)